



For easy specifying/product detailing, copy and paste the text below.

Draft Specification

Product name: ModWood

Profiles: Mini Board 68 x 17 mm Solid Decking 88 x 23 mm Wide Decking 137 x 23 mm Marina Board 137 x 32 mm Flame Shield 137 x 23 mm	Colours: Black Bean Jarrah Sahara Silver Gum	Finishes: # Brushed Smooth # Read below
---	---	---

Fixing:

Installation to be in accordance with ModWood's specifications (refer to web site) and relevant building codes. If using KlevaKlip please refer to KlevaKlip's fixing instructions, www.klevaklip.com.au

As ModWood expands in heat and sun, to avoid building stress into the boards and having possible lengthways shrinkage, it is best to fix the boards when the ambient temperature is less than 25°C and when the boards are not sitting in full sun (see "coefficient of thermal linear expansion" on our web site).

Storage & Handling:

ModWood packs should be stored in a dry, flat area under roof and off the ground. Loose boards should be stored on its edge in a dry, flat area under roof and off the ground. Failure to keep packs dry in storage can lead to the growth of mould spores on boards. When moving product, ModWood should be carried on its edge. Please note ModWood is a finished product – take care.

Manufacturer:

ModWood Technologies Pty Ltd

Ph: 03 9357 8866

Email: info@modwood.com.au

Website: www.modwood.com.au

All decking boards are reversible:

- The lighter side of the board is the brushed side. *We have lightly sanded this side.*
- The darker side is known as smooth even though this side also has a texture on it. *We have not sanded this side.*
- Both sides have the same emboss and grip. (88mm R10 / 137mm R11)
- Further information at www.modwood.com.au/frequently-asked-questions

May 2017

